

Washing Machine Inlet Hoses

W046G Washing Machine Inlet Hose

Inlet hose $\frac{3}{4}$ inch BSP thread both ends. (as used on Australian taps), 1.5m long and some longer



W102K Washing Machine Inlet Hose for USA Valve/washing Machines:

Whirlpool, Maytag, Kleanmaid, Speedqueen etc.

Hoses come with rubber washers, filter washer are extra, but are not needed as the valve has a filter.

The blue end (valve end) has a rubber washer, the white end (tap end) has a choice of a rubber or filter washer depending on your selection. Will be an advantage with dirty water (Not clay etc.) that can be filtered out.



W032 Braided hose 2,400kPa (350psi) burst pressure (main pressure is 800-1,000kPa) Extra strong burst resistant hoses. No Longer available, some used one available.



Warning

Inlet hose for American washing machines have a different thread. These hoses have a 3/4 inch USA tap thread at valve end and a 3/4 inch BSP (used in Australian taps) at tap end. The USA tap thread is coarser than Australian taps. Use on Whirlpool, Maytag, Kleanmaid, SpeedQueen and some Asian machine for the US market. Do not force the wrong thread on a fitting as damaged will result! (USA inlet hose sold on this listing)

Postage

One hose P&P1/2(small satchel), two hoses P&PM (Medium satchel)

Note Only one hose will fit into the small satchel due to volume of hoses.

Service notes Use this information at own risk,

Hoses tend to leak at tap or valve, the plastic hose shrinks and the metal crimp now does hold it tight. Note the nuts only have to be hand tight. Do not put tape on the tread, they seal on the rubber washer!